



IP VANDAL DOMED CAMERA



- ▶ Smart UPnP
- ▶ Support 3GPP function
- ▶ Support Network control
- ▶ Weatherproof protection of the housing-IP66
- ▶ Aluminum base, shock-resistant shield, unbreakable housing

MODEL NO.		NT-VDMS-P	NT-VDHS-P
Scanning System	NTSC	525 lines 2:1 interlace	
	PAL	625 lines 2:1 interlace	
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)	
	PAL	15,625Hz(H) , 50Hz(V)	
Effective Pixel	NTSC	510(H) x 492(V)	768(H) x 492(V)
	PAL	500(H) x 582(V)	752(H) x 582(V)
Image Device	1/3" SONY Super HAD CCD		
Horizontal Resolution	420 TV lines		520 TV lines
Sensitivity	0.2Lux		0.5Lux
Signal to Noise	More than 48dB		
Gain Control	Auto		
White Balance	Auto 2500-9500°K		
Lens/Focus point	4.3mm(Optional 6mm,12mm)		
Video Output	1.0 Vp-p 75 Ohm		
Protection Class	IP 66		
Power Requirement(± 10%)	DC12V,500mA		
Power Consumption(± 10%)	400mA		
Video In/ Out	BNC 1/1		
Ethernet	10/ 100 Base-T		
Network Protocol	HTTP, TCP/IP, UDP, RTSP/RTP/RTCP, SMTP, FTP, DNS, PPPoE, DHCP, DDNS, NTP		
Smart UPnP	YES		
Video Resolution	NTSC:720x480, 352x240, 176x120, PAL: 720x576, 352x288, 176x144		
Video Frame rate	NTSC: 30fps, PAL : 25fps		
Image Snapshot	YES		
Compression format	MPEG-4 / M-JPEG dual stream		
Motion Detection	YES		
Triggered Action	Mail, FTP		
Security	Password protection		
3GPP (Mobile Surveillance)	Yes, Support ID login mode		
Operating System	Windows 2000, XP, Vista		
Internet Browser	Microsoft IE 6.0 or above (7.0)		
Operation Temp.	Working: -20~+55°C, Storage: -30~+80°C, Humidity:0~95%RH		
Dimension(mm)	142(R) x84(H)		
Weight(N.W)	Approx. 0.7kg		

