



# AVN211 / 211V

## H.264 Network Camera



### ● FEATURES

- Powerful Remote Surveillance on Multiple Mobile Platforms
  - For mobile device platforms, iPad®, iPod®, iPhone®, BlackBerry®, Nokia® Symbian, Windows® Mobile & Android™ (with their built-in web browsers or EagleEyes)
  - For web browsers, Internet Explorer®, Mozilla Firefox®, Apple® Safari®, Google Chrome™ and Opera
  - For operating systems, Windows & Mac
  - For multiple device control, our CMS software, Video Viewer, is provided for free
- Low-latency video streaming with H.264 compression format for sharp and clear images
- Hybrid digital / analog video output
- It is friendly to use by wizard with browser
- Motion detection
- Free CMS software with E-Map for multiple devices control & surveillance
- (AVN211V Only) ONVIF standard supported to simplify system integration

### ● SPECIFICATIONS

	AVN211	AVN211V
<b>■ Network</b>		
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP	
ONVIF Support	NO	YES
Frame Rate	NTSC:30, PAL:25	
Number of Online Users	10	
Security	Multiple user access levels with password / IP address filtering	
Web management	(1) The licensed software "Video Viewer" for up to 16 network cameras control simultaneously (2) AJAX management user interface for web browser	
<b>■ Video</b>		
Video Compression	H.264 / MPEG4 / MJPEG	
Video Remote Control	YES	
Video Adjustment	Brightness, Contrast, Saturation and Hue	
Mobile	Supports 3GPP mobile surveillance	

## ● SPECIFICATIONS (CONTINUED...)

	AVN211	AVN211V
<b>■ Camera</b>		
Image Sensor	1/3" H.R. CCD image sensor	
Pixels	768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL>	
Lens	f4.6mm	
F-number	F1.9	
Viewing Angle	60°	
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.	
Min Illumination	1 Lux	
Video Output	1.0 Vp-p. 75Ω	
BLC	AUTO	
White Balance	ATW	
<b>■ Others</b>		
Mobile Surveillance	iPad, iPod, iPhone, BlackBerry, Windows Mobile, Symbian & Android	
Remote Control	YES	
Motion Detection	YES	
Power	DC12V, 0.5A	
Operating Temperature	0~40°C	
Humidity	85%	
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> <li>● Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD</li> <li>● 256 MB RAM</li> <li>● AGP graphics card, Direct Draw, 32MB RAM</li> <li>● Windows 7, Vista &amp; XP, DirectX 9.0 or later</li> <li>● Internet Explorer 7.x or later</li> </ul>	
Dimension (mm)**	152.5(L) x 115.2(W) x 40.2(H) (6.00" x 4.54" x 1.58")	
Shipping Weight	812g (1.79 lbs) including mounting bracket and power supply	
In/Out Door Use	Indoor	

\* The specifications are subject to change without notice.

\*\* Dimensional tolerance: (± 5mm)

## ● Dimensions (mm)

152.5 (L) x 115.2 (W) x 40.2 (H)

