

H.264 4 / 8 / 16 CH DVR (HT SERIES)

MADE IN TAIWAN



- ▶ H.264 Algorithm hardware compression
- ▶ Full Graphic User Interface (Multiple language support)
- ▶ Software Deinterlacer upon live and playback
- ▶ Support Multiple language for camera title
- ▶ Individual Channel Recording Setup (Resolution, Frame rates and Quality)
- ▶ VGA Output with a Deinterlace
- ▶ Dual Video Streaming, One for Local Record and the Other for Network Transmission
- ▶ Support playback preview mode
- ▶ User define PTZ tour
- ▶ Support image Import form USB device
- ▶ Support 3G mobile phone (live view)

MODEL NO.		HT-04120	HT-08120	HT-16240
Camera Input		4 BNC	8 BNC	16 BNC
Video Output		1 BNC and 1 VGA, selectable	1 BNC / 1 VGA	
Audio Input / Output		4 RCA /1 RCA		
Sensor In /Alarm out		1(NC, NO selectable)/ 1(Relay Output)		
Operating System		Embedded Linux OS		
Display Speed		Real Time		
Display Resolution		720 X 480(NTSC), 720 X 576(PAL)		
Display Split Screen		1,4, Sequence	1,4,6,8,9, Sequence	1,4,6,8,9,13,16, Sequence
Compression Format		H.264 (DSP)		
Picture Quality		4 LEVEL (Super, High, Medium, Low)		
Recording Speed	NTSC	120 FPS(CIF)	127 FPS(CIF)	135 FPS (CIF)
		60 FPS(Half-D1) + 3 FPS(CIF)	60 FPS(Half-D1) + 7 FPS(CIF)	60 FPS(Half-D1) + 15 FPS(CIF)
		30 FPS(D1) + 3 FPS(CIF)	30 FPS(D1) + 7 FPS(CIF)	30 FPS(D1) + 15 FPS(CIF)
	PAL	100 FPS(CIF)	107 FPS(CIF)	115 FPS(CIF)
		50 FPS(Half-D1) + 3 FPS(CIF)	50 FPS(Half-D1) + 7 FPS(CIF)	50 FPS(Half-D1) + 7 FPS(CIF)
		25 FPS(D1) + 3 FPS(CIF)	25 FPS(D1) + 7 FPS(CIF)	25 FPS(D1) + 7 FPS(CIF)
Playback Display		1,4	1,4,8	1,4,8,16
Search Mode		Calendar, Event		
Playback Speed		Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64,x1/2,x1/4], Frame to frame, Pause		
Network Interface		Ethernet, PPPoE		
Network Protocol		TCP/IP, HTTP, DHCP		
Application		Windows 2000 / XP / Vista (PC Client system& IE)		
Web Browser		Internet Explorer		
Backup		Network, USB 2.0Thumb Drive		
HDD		Supports 1 SATA HDD	Supports 2 SATA HDDs	
Power Consumption		12V / 3.3A	12V / 5A	
Operating Temperature		5 ~40(41~104F)		
Relative Humidity		Maximum 80% non-condensing		
Dimension(mm)		337(W) x 256(D) x 60(H)		
Weight(N.W)		Approx. kgs (W/O HDD)		